



Safety Data Sheet

24 Hour Emergency Phone Numbers
Medical/Poison Control:
In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-5053
1-352-323-3500

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

Product Name:	DAP High Temp 100% RTV Silicone Sealant	Revision Date:	1/3/2019
Product UPC Number:	070798080133	Supercedes Date:	3/15/2017
Manufacturer:	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	Product Use/Class:	Caulking Compound
		SDS No:	00015008001
		Preparer:	Regulatory and Environmental Affairs
	SDS Coordinator: MSDS@dap.com		
	Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222		

2. Hazards Identification

GHS Classification

Not a hazardous substance or mixture.

Symbol(s) of Product

None

Signal Word

Not a hazardous substance or mixture.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Hydrotreated middle distillate	64742-46-7	3-7	GHS07	H332
Silica, amorphous	7631-86-9	3-7	GHS07	H332
Aluminum	7429-90-5	1-5	GHS02-GHS06	H228-250-261-312-331
Titanium dioxide	13463-67-7	0.5-1.5	No Information	No Information
Carbon black	1333-86-4	0.1-1.0	GHS02	H251

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling. Remove contact lenses before using. Do not handle contact lenses until all sealant has been cleaned from fingertips, nails and cuticles. Residual sealant may transfer to contact lenses and cause severe eye irritation.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Hydrotreated middle distillate	N.E.	N.E.	N.E.	N.E.
Silica, amorphous	N.E.	N.E.	N.E.	N.E.
Aluminum	1 mg/m ³ TWA	N.E.	15 mg/m ³ TWA	N.E.
	respirable particulate matter		total dust, 5 mg/m ³ TWA respirable fraction	
Titanium dioxide	10 mg/m ³ TWA	N.E.	15 mg/m ³ TWA	N.E.
Carbon black	3 mg/m ³ TWA	N.E.	total dust 3.5 mg/m ³ TWA	N.E.
	inhalable particulate matter			

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Wear nitrile or neoprene gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Appearance:	Red	Physical State:	Paste
Odor:	Acetic Acid	Odor Threshold:	Not Established
Density, g/cm³:	1.01 - 1.01	pH:	Not Applicable
Freeze Point, °C:	Not Established	Viscosity (mPa.s):	Not Established
Solubility in Water:	No Information	Partition Coeff., n-octanol/water:	Not Established
Decomposition Temperature, °C:	Not Established	Explosive Limits, %:	N.E. - N.E.
Boiling Range, °C:	100 - 100	Auto-Ignition Temperature, °C	Not Established
Minimum Flash Point, °C:	100	Vapor Pressure, mmHg:	Not Established
Evaporation Rate:	Slower Than n-Butyl Acetate	Flash Method:	Seta Closed Cup
Vapor Density:	Heavier Than Air	Flammability, NFPA:	Non-Flammable
Combustible Dust:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Oxidizing agents. Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. During application and cure, this product releases acetic acid. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion may result in obstruction when material hardens.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause mild irritation of eyes and skin.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-46-7	Hydrotreated middle distillate	7400 mg/kg Rat	>2000 mg/kg Rabbit	>20 mg/L
7631-86-9	Silica, amorphous	>3300 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L
7429-90-5	Aluminum	>2000 mg/kg Rat	2000 mg/kg Rat	7.6 mg/l Rat
13463-67-7	Titanium dioxide	>10000 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L
1333-86-4	Carbon black	>15400 mg/kg Rat	N.I.	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

14. Transport Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name:	Not Regulated
DOT Technical Name:	N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

15. Regulatory Information

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Aluminum	7429-90-5

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information

Revision Date: 1/3/2019 **Supersedes Date:** 3/15/2017

Reason for revision: Substance and/or Product Properties Changed in Section(s):

01 - Product Information
 02 - Hazards Identification
 05 - Flammability Information
 09 - Physical & Chemical Information
 11 - Toxicological Information
 13 - Disposal Information
 14 - Transportation Information
 15 - Regulatory Information
 16 - Other Information
 Substance Regulatory CAS Number Changed
 Substance Hazardous Flag Changed
 Substance Hazard Threshold % Changed
 Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
1	0	0	X

VOC Less Water Less Exempt Solvent, g/L: 30.2

VOC Material, g/L: 30

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 2.95

VOC Actual, Wt/Wt%: 3.0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H228	Flammable solid.
H250	Catches fire spontaneously if exposed to air.
H251	Self-heating: may catch fire.
H261	In contact with water releases flammable gases.
H312	Harmful in contact with skin.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS06



GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.