



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® DYNAGRIP® Projects

PRODUCT DESCRIPTION

DAP® DYNAGRIP® Projects construction adhesive is designed to bond common building materials. This easy to apply formula meets ASTM C557 and provides a weather resistant bond once fully cured.



PACKAGING	COLOR	UPC
9 oz	White	7079827504
27 oz	White	7079827505

KEY FEATURES & BENEFITS

- Easy Water Clean Up
- Low Odor
- Easy to Gun
- VOC Compliant

PERFORMANCE CHARACTERISTICS

- Meets ASTM C557 specification for drywall installation
- Interior use

SUGGESTED USES

Adheres to:

- Brick /Masonry/ Concrete
- Drywall / Foamboard
- Ceramic Tiles
- Cove Base



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Dimensional Lumber
- Plywood / OSB / FRP

FOR BEST RESULTS

- Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning.
- For square surfaces apply around perimeter and “X” shaped bead. For long surfaces use “S” shaped bead. Press firmly into place. One surface must be porous.
- Store away from extreme heat or cold.

APPLICATION

1. Surfaces must be clean, structurally sound, and free of debris.
2. Pre-cut and fit materials before applying adhesive.
3. Trim nozzle to desired bead size. 1/4” recommended for most applications.
4. Load cartridge into applicator gun.
5. Apply a continuous bead to desired surface.
6. Within 10 minutes, position and press substrates firmly into place.
7. Certain applications may require mechanical fasteners.
8. Allow to dry for 48 hours

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Base Polymer:	Acrylic Latex
Bead Color	Tan
Weight % Solids	68%
Odor	Mild solvent
Clean Up	Mineral spirits
Flash Point	80°F
Shelf Life	18 months
Coverage	9oz: 1/4” bead yields 27 linear ft., 3/8” bead yields 12 linear ft. 27oz: 1/4” bead yields 82 linear ft., 3/8” bead yields 36 linear ft
Typical Application Properties	
Application Temperature Range:	40°F – 100°F
Tooling Time (Working Time)	15 minutes



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Full Cure Time	48 hours
Typical Cured Performance Properties	
Service Temperature Range:	0°F – 140°F
Calif. ARB VOC	<0.8% Wt/Wt
VOC Less Exempt Less Water	VOC less Water, less Exempt Solvent: <32 g/L

CLEAN UP & STORAGE

Uncured adhesive: use mineral spirits to clean up wet adhesive from surface and tools, following solvent manufacturer's precautions. Cured adhesive must be cut or scraped away.

SAFETY

May be harmful if swallowed or in contact with skin. May cause eye, skin, nose, throat and respiratory tract irritation. Avoid breathing vapors. Use only with adequate ventilation. Ensure fresh air entry. Avoid contact with eyes, skin and clothing. Wear rubber gloves and eye protection with side shields.

FIRST AID: SKIN CONTACT: Wash skin thoroughly with soap and water. EYE CONTACT: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately if complications arise from exposure. FOR EMERGENCIES, call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN**

See product label or Safety Data Sheet for health and safety information. You can request a SDS sheet by calling 888-DAP-TIPS or by visiting our website at dap.com.

WARRANTY

LIMITED WARRANTY: If product fails to perform when used as directed, within one year of date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com