



DYNAGRIP®

THE GRIP THAT OUTPERFORMS™

Technical Data Bulletin

DRYWALL

Construction Adhesive

DAP® DYNAGRIP® DRYWALL construction adhesive is a premium grade adhesive specifically formulated for drywall installation. This VOC compliant, instant grab adhesive prevents nail pops and helps limit air and sound movement between walls. DYNAGRIP® DRYWALL is an easy to gun adhesive that delivers a strong permanent bond.



**STRONG
PERMANENT
BOND**



**INSTANT
GRAB**



**EASY
TO GUN**

Recommended For:

- Drywall & Interior Paneling Installation

Adheres To:

- Dimensional Lumber
- Drywall
- Masonry
- Metal
- OSB
- Paneling
- Plywood
- Wood

Not Recommended For:

- Bonding two non-porous materials
- Constant water exposure
- Exterior use
- Flooring applications
- Mirror installation
- Subfloor or deck installation
- Applications other than drywall & paneling installation

DAP Products, Inc.
2400 Boston Street, Suite 200
Baltimore, MD 21224
Phone: 410-675-2100
REV: 11/01/2016

SKU #	SIZE
7079827518	28oz



CAUTION!
Read back panel carefully for cautions.
¡PRECAUCIÓN!
Lea cuidadosamente el panel posterior sobre otras precauciones.
28 FL.OZ. (828 mL)



DYNAGRIP
THE GRIP THAT OUTPERFORMS™

DRYWALL

Product Features

- Exceeds ASTM C557
- Easy Water Clean Up
- Low Odor
- VOC Compliant

Directions

FOR BEST RESULTS: Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning. One surface must be porous. Store away from extreme heat or cold.

INSTRUCTIONS: 1. Surfaces must be clean, structurally sound, and free of debris. 2. Pre-cut and fit materials before applying adhesive. 3. Trim nozzle to desired bead size. 1/4" recommended for most applications. 4. Puncture inner foil seal. 5. Load cartridge into applicator gun. **DRYWALL:** 1. Apply a continuous bead to furring strips, wall studs, or backer material. 2. Within 20 minutes, position and press drywall firmly into place. 3. Brace as needed and apply mechanical fasteners per local code requirements. 4. Allow to dry for 24 hours. **PANEL:** 1. Apply a continuous bead to furring strips, studs, or backer material, apply "S" shaped bead to rear side of panels. 2. Within 20 minutes, position and press panels firmly into place. 3. Apply mechanical fasteners and brace as needed. 4. Allow to dry for 24 hours.

CLEAN UP: Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

USAGE INFORMATION: For usage information or warranty information, please contact DAP Technical Customer Service at 888-DAP-TIPS or visit dap.com & click on "Ask the Expert".

Contains: Ethylene glycol and urea.

May be harmful if swallowed or in contact with skin. May cause eye, skin, nose, throat and respiratory tract irritation. Avoid breathing vapors. Use only with adequate ventilation. Ensure fresh air entry. Avoid contact with eyes, skin and clothing. Wear rubber gloves and eye protection with side shields.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: SKIN CONTACT: Wash skin thoroughly with soap and water. EYE CONTACT: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: **DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **For emergencies,** call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com.

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

TYPICAL PHYSICAL PROPERTIES

- Type: Synthetic Latex
- Application Temperature: 40°F to 100°F
- Service Temperature: 0°F to 140°F
- Bead Color: Off White
- Solids: 66-70%
- Shelf Life: 18 months
- Skin Time: 20 minutes
- Cure Time: 7 days
- Coverage:
 - 28oz: 1/4" bead yields 86 linear ft., 3/8" bead yields 38 linear ft.
- Specifications:
 - ASTM C557 Exceeds.
- Calif. ARB VOC <0.8% Wt/Wt
- VOC Content: VOC less Water, less Exempt Solvent: <32 g/L