



DYNAGRIP®
THE GRIP THAT OUTPERFORMS™

Technical Data Bulletin

TUB SURROUND

Construction Adhesive

DAP® DYNAGRIP® TUB SURROUND construction adhesive is a premium grade, high strength adhesive specifically formulated for tub surround installation. This premium adhesive is safe for use on all tub surround materials and dries clear for an ideal finish. DYNAGRIP® TUB SURROUND is an instant grab adhesive that is moisture, steam, water, and heat resistance once fully cured.



SHOWER SAFE



**DRIES CLEAR
FOR AN
IDEAL FINISH**



**STRONGER
HOLDING
POWER**

Recommended For:

- Tub Surround Installation
- Shower Wall Enclosures

Adheres To:

- ABS Tub Surrounds
- Acrylic Tub Surrounds
- Cement Backerboard
- Ceramic Tiles
- Dimensional Lumber
- Drywall
- Fiberglass Tub Surrounds
- Foamback Tub Surrounds
- Greenboard
- OSB
- Plywood
- PVC Tub Surrounds

Not Recommended For:

- Mirror installation
- Bonding two non-porous materials
- Applications other than tub surround & water enclosure installation

DAP Products, Inc.
2400 Boston Street, Suite 200
Baltimore, MD 21224
Phone: 410-675-2100
REV: 11/01/2016

SKU #	SIZE
7079827521	10.3oz



CAUTION!
Read back panel carefully for cautions.
¡PRECAUCIÓN! Lea cuidadosamente
el panel posterior sobre otras precauciones.
10.3 FL. OZ. (305 mL)



DYNAGRIP
THE GRIP THAT OUTPERFORMS™

TUB SURROUND

Product Features

- **Won't Etch Or Burn Tub Surround Material**
- **Instant Grab**
- **Easy Water Clean Up**
- **VOC Compliant**

Directions

FOR BEST RESULTS: Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning. One surface must be porous. Store away from extreme heat or cold.

INSTRUCTIONS: 1. Surfaces must be clean, structurally sound, and free of debris. 2. Pre-cut and fit materials before applying adhesive. 3. Trim nozzle to desired bead size. ¼" recommended for most applications. 4. Puncture inner foil seal. 5. Load cartridge into applicator gun. 6. Apply a continuous bead to studs or backer substrate, adhesive may also be applied to back of tub surround panel according to tub surround manufacturers installation instructions. 7. Within 10 minutes, position and press panels firmly into place. 8. Allow to dry for 24 hours before exposing to water or moisture.

CLEAN UP: Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

USAGE INFORMATION: For usage information or warranty information, please contact DAP Technical Customer Service at 888-DAP-TIPS or visit dap.com & click on "Ask the Expert".

DANGER: Contains: Ethylene glycol.

May be harmful if swallowed or in contact with skin. May cause eye, skin, nose, throat and respiratory tract irritation. Avoid breathing vapors. Use only with adequate ventilation. Ensure fresh air entry. Avoid contact with eyes, skin and clothing. Wear rubber gloves and eye protection with side shields.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: SKIN CONTACT: Wash skin thoroughly with soap and water. EYE CONTACT: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: **DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **For emergencies,** call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com.

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

TYPICAL PHYSICAL PROPERTIES

- Type: Synthetic Latex
- Application Temperature: 40°F to 100°F
- Service Temperature: 0°F to 140°F
- Bead Color: White
- Solids: 51%
- Shelf Life: 18 months
- Skin Time: 15 minutes
- Cure Time: 7 days
- Coverage:
 - 10.3oz: ¼" bead yields 32 linear ft., 3/8" bead yields 14 linear ft.
- Calif. ARB VOC <1% Wt/Wt
- VOC Content: VOC less Water, less Exempt Solvent: <50 g/L