



## Technical Data Bulletin

# PROJECTS

### Construction Adhesive

DAP® DYNAGRIP® PROJECTS construction adhesive is designed to bond common building materials. This easy to apply formula meets ASTM C557 and provides a weather resistant bond once fully cured.

#### Recommended For:

- Decorative Paneling & Molding
- Cove Base & Base Board Installation
- Foam Insulation Panels
- Interior Repair Projects
- Drywall Installations

#### Adheres To:

- Brick
- Concrete
- Cove Base
- Ceramic Tiles
- Drywall
- Dimensional Lumber
- Foamboard
- FRP
- Masonry
- OSB
- Plywood

#### Not Recommended For:

- Bonding two non-porous materials
- Constant water exposure
- Exterior use
- Flooring applications
- Mirror installation
- Subfloor or deck installation

DAP Products Inc.  
2400 Boston Street, Suite 200  
Baltimore, MD 21224  
Phone: 410-675-2100  
REV: 12/11/2017

SKU #	SIZE
7079827504	9 oz
7079827505	27 oz





**DYNAGRIP**  
THE GRIP THAT OUTPERFORMS™

## PROJECTS

### Product Features

- Easy Water Clean Up
- Low Odor
- Easy To Gun
- VOC Compliant

### Directions

**FOR BEST RESULTS:** Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning. For square surfaces apply around perimeter and “X” shaped bead. For long surfaces use “S” shaped bead. Press firmly into place. One surface must be porous. Store away from extreme heat or cold.

**INSTRUCTIONS:** 1. Surfaces must be clean, structurally sound, and free of debris. 2. Pre-cut and fit materials before applying adhesive. 3. Trim nozzle to desired bead size. ¼” recommended for most applications. 4. Load cartridge into applicator gun. 5. Apply a continuous bead to desired surface. 6. Within 10 minutes, position and press substrates firmly into place. 7. Certain applications may require mechanical fasteners. 8. Allow to dry for 48 hours.

**CLEAN UP:** Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

**USAGE INFORMATION:** For usage information or warranty information, please contact DAP Technical Customer Service at 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on “Ask the Expert”.

Contains: Ethylene glycol

May be harmful if swallowed or in contact with skin. May cause eye, skin, nose, throat and respiratory tract irritation. Avoid breathing vapors. Use only with adequate ventilation. Ensure fresh air entry. Avoid contact with eyes, skin and clothing. Wear rubber gloves and eye protection with side shields.

**FIRST AID:** SKIN CONTACT: Wash skin thoroughly with soap and water. EYE CONTACT: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: **DO NOT INDUCE VOMITING.** Get medical attention immediately if complications arise from exposure. **FOR EMERGENCIES,** call poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit [dap.com](http://dap.com).

**KEEP OUT OF REACH OF CHILDREN.**

### TYPICAL PHYSICAL PROPERTIES

- Type: Acrylic Latex
- Application Temperature: 40°F to 100°F
- Service Temperature: 0°F to 140°F
- Bead Color: Tan
- Solids: 68%
- Shelf Life: 18 months
- Skin Time: 15 minutes
- Cure Time: 48 hours
- Coverage:
  - 9oz: ¼” bead yields 27 linear ft., 3/8” bead yields 12 linear ft.
  - 27oz: ¼” bead yields 82 linear ft., 3/8” bead yields 36 linear ft.
- Specifications:
  - ASTM C557 Meets or Exceeds.
- Calif. ARB VOC <0.8% Wt/Wt
- VOC Content: VOC less Water, less Exempt Solvent: <32 g/L